



37U Series DFK 37AUX273

- IMX273 CMOS Pregius Sensor
- 1.6 MP
- USB3 Vision / UVC compliant
- Trigger and I/Os
- C/CS mount

USB[®]
VISION

The 37U series camera DFK 37AUX273 with a Sony IMX273 sensor delivers 238 frames per second with a resolution of 1440x1080 (1.6 MP).

37U Series: Featuring a range of Sony and onsemi sensors with resolutions up to 12MP, these cost-optimized, single-board industrial cameras are available in several form factor variants, providing a flexible customization concept for systems engineers and OEMs. These streamlined, standard-feature cameras offer a reduced hardware footprint with USB-C connector and optional hardware trigger and I/Os.

The USB3 Vision standard allows for rapid integration into new and existing applications via The Imaging Source's [IC Imaging Control 4 SDK](#) as well as most other third-party image processing libraries.

Note: This Data Sheet is intended to provide a summary overview for an individual camera model. The Imaging Source's website also offers information on spectral sensitivity, dimensional diagrams, sensor data sheets, STEP files as well as our full product catalog. For comprehensive technical information, please refer to the Technical Reference Manual specific to each camera model.

www.theimagingsource.com

1 Quick Facts

General	
Vision Standard	USB3 Vision (UVC compliant)
Dynamic Range	10 bit
Resolution	1440x1080
Frame Rate at Full Resolution	238

Optical Interface	
IR-Cut filter	Yes
Sensor Type	Sony IMX273LQR-C
Shutter Type	Global
Sensor Format	1/2.9 inch
Pixel Size	3.45 μm
Lens Mount	C/CS



Electrical Interface	
Interface	USB 3.1gen1
Supply Voltage	4.75 VDC to 5.25 VDC
Current Consumption	approx 380 mA @ 5 VDC

Mechanical Data	
Dimensions	H: 36 mm, W: 36 mm, L: 25 mm
Mass	70 g

Environmental Conditions	
Housing Temperature (operating)	-5 °C to 50 °C
Temperature (storage)	-20 °C to 80 °C
Humidity (operating)	20 % to 80 % (non-condensing)
Humidity (storage)	20 % to 95 % (non-condensing)

2 Dimensional Diagrams

2.1 DFK 37AUX273 C-Mount without Tripod Adapter




Dimensions: mm
Tolerances: DIN ISO 2768-f



3 Spectral Characteristics

3.1 IR-Cut Filter



3.2 Spectral Sensitivity - IMX273LQR-C

